


**Veri sayfası (2021-05-28)**
**Airfix P 2 - 300**

Kapalı soğutmalı ve ısıtmalı su sistemlerinde içme suyu uygulamaları için genleşme tankları.



Tip	Hacim [l]	Ön basınç [bar]	Boyutlar		Bağlantı	Membran	Ağırlık [kg]		Sipariş Kodu
			Ø [mm]	H. [mm]					
Airfix P 2 - 3.5 bar	2	3,5	120	235	G 1/2" M	Butyl	4,6*	336	24850
Airfix P 3 - 3.5 bar	3	3,5	170	240	G 3/4" M	Butyl	1,5	168	24851
Airfix P 5 - 3.5 bar	5	3,5	170	275	G 3/4" M	Butyl	1,7	144	24852
Airfix P 8 - 3.5 bar	8	3,5	220	305	G 3/4" M	Butyl	2,2	90	24853
Airfix P 12 - 3.5 bar	12	3,5	260	310	G 3/4" M	Butyl	2,9	72	24854
Airfix P 16 - 3.5 bar	16	3,5	260	345	G 3/4" M	EPDM	3,4	60	24855
Airfix P 18 - 3.5 bar	18	3,5	260	375	G 3/4" M	EPDM	3,5	60	24856
Airfix P 24 - 3.5 bar	24	3,5	260	485	G 3/4" M	EPDM	4,3	56	24857
Airfix P 35 - 3.5 bar	35	3,5	380	470	G 1" M	EPDM	8,0	24	24858
Airfix P 50 - 3.5 bar	50	3,5	380	720	G 1" M	EPDM	9,9	15	24859
Airfix P 60 - 3.5 bar	60	3,5	380	830	G 1" M	EPDM	12,1	15	24860
Airfix P 80 - 3.5 bar	80	3,5	460	760	G 1" M	EPDM	14,0	10	24861
Airfix P 100 - 3.5 bar	100	3,5	460	880	G 1" M	EPDM	16,0	10	24862
Airfix P 150 - 3.5 bar	150	3,5	510	1030	G 1" M	EPDM	25,5	8	24863
Airfix P 200 - 3.5 bar	200	3,5	590	1070	G 1 1/4" M	EPDM	37,5	8	24864
Airfix P 300 - 3.5 bar	300	3,5	650	1250	G 1 1/4" M	EPDM	50,5	3	24865