


Veri sayfası (2021-05-28)

Airfix P 400 - 5000

Kapalı soğutmalı ve ısıtmalı su sistemlerinde içme suyu uygulamaları için genleşme tankları.



Tip	Hacim [l]	Ön basınç [bar]	Boyutlar		Sistem bağlantısı	Membran	Ağırlık [kg]		Sipariş Kodu
			Ø [mm]	H [mm]					
Airfix P 400 - 3.5 bar	400	3,5	790	1287	G 1 1/4" M	EPDM	84	3	24933
Airfix P 600 - 3.5 bar	600	3,5	790	1647	G 1 1/4" M	EPDM	106	1	24934
Airfix P 800 - 3.5 bar	800	3,5	790	1994	G 1 1/4" M	EPDM	145	1	24935
Airfix P 1000 - 3.5 bar	1000	3,5	790	2345	G 1 1/4" M	EPDM	167	1	24936
Airfix P 1500 - 3.5 bar	1500	3,5	1000	2510	Rp 2 1/2"	Butyl	423	1	24869
Airfix P 2000 - 3.5 bar	2000	3,5	1100	2745	Rp 2 1/2"	Butyl	483	1	24870
Airfix P 2500 - 3.5 bar	2500	3,5	1100	3295	Rp 2 1/2"	Butyl	537	1	24871
Airfix P 3000 - 3.5 bar	3000	3,5	1200	3425	Rp 2 1/2"	Butyl	766	1	24872
Airfix P 5000 - 3.5 bar	5000	3,5	1500	3615	Rp 2 1/2"	Butyl	1620	1	24873



Avantajları

- Factory tested prior to dispatch.